

MOTOREDUKTOR: NMRV-075-100B14

WIDOK 3D



DANE TECHNICZNE I WYMIARY

GR Size	075
PAM Input PAM flange	100/112 B14
ACU Output hole shaft (d)	28
VB Double input shaft	NO
TFU Output flange gear unit 2	NO
DFU Output flange dimension (d)	-
PFU Output flange position	-
AL Output hole shaft (d)	NO
PAL Output shaft position	-
BR Torque arm	NO
PBR Torque arm position	-
CAP Cover	NO
TIP Motor type	T-Three phase
GRA Motor size	100
RAF Cooling	IC411-Self-Ventilated
FC Motor execution	B14
TF Break type	-
AF Brake power supply	-
COP Terminal box cover	Aluminium
CVE Fan cover	Standard
MOR Terminal box cover position	1
A	120
AC	191
B	50
B1	8
BB	8(10)
BM	8
BM1	8
D	28(35)
D1	24

DM	28
DM1	28
E	60
F	M8
FF	M10x22
G	112.5
G1	120
H	86
I	75
K	90
KE	M8x14(8)
L	112
LB	308
LL	368
M	115
N	95
N1	57
O	11.5
P	140
PM	160
PM1	160
Q	93
R	119
S	10
T	40
T1	27
TM	31.3
TM1	31
TT	31.3(38.3)
V	60
W	45°

WIDOK 2D



AKCESORIA

