

MOTOREDUKTOR: NMRV-110-80B5

WIDOK 3D



DANE TECHNICZNE I WYMIARY

GR Size	110
PAM Input PAM flange	80B5
ACU Output hole shaft (d)	42
VB Double input shaft	NO
TFU Output flange gear unit 2	NO
DFU Output flange dimension (d)	-
PFU Output flange position	-
AL Output hole shaft (d)	NO
PAL Output shaft position	-
BR Torque arm	NO
PBR Torque arm position	-
CAP Cover	NO
TIP Motor type	T-Three phase
GRA Motor size	080
RAF Cooling	IC411-Self-Ventilated
FC Motor execution	B5
TF Break type	-
AF Brake power supply	-
COP Terminal box cover	Aluminium
CVE Fan cover	Standard
MOR Terminal box cover position	1
A	170
AC	158
B	60
B1	8
BB	12
BM	6
BM1	6
D	42
D1	28

DM	19
DM1	19
E	40
F	M10
FF	M6x16
G	160
G1	155
H	127.5
I	110
K	115
KE	M10x18(8)
L	144
LB	232.5
LL	272.5
M	165
N	130
N1	74
O	14
P	200
PM	200
PM1	200
Q	125
R	167.5
S	14.5
T	50
T1	31
TM	21.8
TM1	21.5
TT	45.3
V	85
W	45°

WIDOK 2D



AKCESORIA

